



ZENITH ENGINEERING PTE LTD (197904024Z)
No 34 Joo Koon Circle Jurong Town Singapore 629060
Tel: (65) 6861 1100 Fax: (65) 6862 1948 email: info@ze.com.sg website: www.ze.com.sg

IG ZENITH SDN BHD (480123-H)
Lot 6975, Batu 12, Jalan Balakong, 43300 Balakong, Selangor, Malaysia
Mailing Address : PO Box 104, 43300 Seri Kembangan, Selangor, Malaysia
Tel: (60-3) 8962 1060/61 Fax: (60-3) 8962 1062

Phoenix Refuse Collection Vehicle (Rear End Loader)

Project Ref : ZP3880JK Delrld : Aug2010

Pictured below Model P2-20, 21m3 body volume on 28MT GVW chassis



Chassis WB : 4,875mm (1st to boogie-center) O/A Dim: L x B x H = 9,565 x 2,530 x 3,420mm (width varies depending on binlifter) .
Typical unladen weight of REL body& tailgate approx 6,580kg (based on weigh bridge ticket) plus BLT100 binlifter of 360kg.



LTA approved Amber-colour light-bar.

Electrical Controls include single or continuous-packing cycles. Manual controls for binlifter and hopper-cover.

Engine throttling ONLY when operating any of the controls (engine idles when hydraulics are not operated even when PTO is engaged to conserve fuel).



Features & Upgrades included for this particular project :

- if rear-standing platform is not-raised, forward speed is limited to 20km/hr and reversing is disabled.
- Front Amber Light-bar is disabled when speed exceeds 20km/hr.
- Hydraulically operated aluminum hopper-cover
- HARDOX double-layer hopper wear-plate (6+4mm)
- S/S 304 leachate tanks under body.

Large-sized foldable rear-platform interlock with speed and reversing.

